

## Data sheet

### PS 207 (207-2BA20)

#### Technical data

<b>Order no.</b>	<b>207-2BA20</b>
Type	PS 207

#### General information

Note	-
Features	AC 100...240 V w/o manual intervention Output voltage DC 24 V Terminal module with 2x11 clamps

#### Technical data power supply

Input voltage (rated value)	AC 100...240 V
Input voltage (permitted range)	AC 100...240 V
Mains frequency (rated value)	50...60 Hz
Mains frequency (permitted range)	47...63 Hz
Input current (at 120 V)	0.53 A
Input current (at 230 V)	0.24 A
Inrush current (at 25 °C)	30 A
I <sup>2</sup> t	1 A <sup>2</sup> s
Power consumption typ.	53 W
Output voltage (rated value)	24 V
Output current (rated value)	2 A
Power supply parallel switchable	yes
Protect type	Short circuit, overload, over temperature
Ripple of output voltage (max.), BW=20 MHz	100 mV
Efficiency typ.	90 %
Power loss typ.	5 W

#### Clamp parameter

Terminal voltage max.	DC 60 V
Terminal current max.	10 A

#### Status information, alarms, diagnostics

Status display	yes
Interrupts	no
Process alarm	no
Diagnostic interrupt	no
Diagnostic functions	no
Diagnostics information read-out	none
Supply voltage display	none
Group error display	none
Channel error display	none

#### Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

#### Mechanical data

Dimensions (WxHxD)	50.8 mm x 76 mm x 78 mm
Weight	210 g

#### Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

#### Certifications

UL certification	-
KC certification	-